

EM038

mATX chassis

EW038



Features

● TAC 2.0 Thermal Solution

Qualified for TAC 2.0, a mass ventilation hole side panel design strengthens thermal efficiency and cools down the entire system.



● Configured up to 7 Drive Bays

Expandable to 5.25" x 2, 3.5" x 3 and optional internal 3.5" drive bay x 2.



● Stamped Motherboard Support

Easy M/B installation – No M/B standoff required.

● Folded Edge -

No sharp edges for safe installation.

● Optional Detachable HDD Cage, Tool-Free Side Panels, ODD Bays and FDD Bay

For easy removal and installation.

CASE SIZE	Mini Tower Chassis
EXTERNAL DRIVE BAY	5.25" x 2, 3.5" x 1
INTERNAL DRIVE BAY	3.5" x 2
FRONT PORTS	USB 2.0 x 2 HD Audio
DIMENSIONS (HxWxD) w/o Front Panel	350 x 190 x 380 mm 13.8" x 7.5" x 15"
M/B	Micro-ATX
I/O EXPANSION SLOTS	PCI-E / PCI / AGP Slot x 4
POWER SUPPLY	ATX 12V Form Factor, PS II
THERMAL SOLUTION	Intel Certified TAC 2.0
SAFETY	Meets RoHS, CE and FCC Class B Requirements
SECURITY	Padlock Loop for Padlock / Kensington Slot
OPTIONAL	Internal HDD Cage for Extra 3.5" Drive Bay x 2 9 or 12cm Rear Fan / Side Panel Clips Chassis Intrusion Switch Tool-Free Drive Bays

Specification