

EM040

mATX chassis

<u>Features</u>

■ TAC 2.0 Thermal Solution -

Qualified for TAC 2.0, a mass ventilation hole side panel design strengthens thermal efficiency and cools down the entire system.



Configured up to 7 Drive Bavs

Expandable to 5.25" x 2, 3.5" x 3 and optional internal 3.5" drive bay x 2.



Stamped Motherboard Support Easy M/B installation – No M/B standoff required. Extra Vent at Rear Panel Optional 9 or 12cm auxiliary cooling fan can be installed at rear panel for better system cooling.

Folded Edge

No sharp edges for safe installation.

 Optional Detachable HDD Cage, Tool-Free Side Panels, ODD Bays and FDD Bays

For easy removal and installation,

| CASE SIZE | Mini Tower Chassis |
|---------------------------------------|--|
| EXTERNAL DRIVE BAY | 5.25" x 2, 3.5" x I |
| INTERNAL DRIVE BAY | 3.5" x 2, 2.5" x 1 |
| FRONT PORTS | USB 2.0 x 2 HD Audio |
| DIMENSIONS (HxWxD) w/o Front Panel | 350 x 190 x 380 mm 13.8" x 7.5" x 15" |
| M/B | Micro-ATX |
| I/O EXPANSION SLOTS | PCI-E / PCI / AGP Slot x 4 |
| POWER SUPPLY | ATX 12V Form Factor, PS ∏ |
| THERMAL SOLUTION | Intel Certified TAC 2.0 |
| SAFETY | Meets RoHS, CE and FCC Class B Requirements |
| SECURITY | Padlock Loop for Padlock / Kensington Slot |
| OPTIONAL | Internal HDD Cage for Extra 3.5" x 2 or 3.5" x 1 + |
| | 2.5" \times 1 / 9 or 12cm Rear Fan / 9cm Front Fan / |
| | Side Panel Clips / Chassis Intrusion Switch / |
| | Tool-Free Drive Bays / USB 3.0 x 2 / |
| | 3.5" to 2.5" HDD/SSD Bracket |
| | |

Specification -

