

Z 675

mATX chassis



Features

● TAC 2.0 Thermal Solution

Qualified for TAC 2.0, a mass ventilation hole side panel design strengthens thermal efficiency and cools down the entire system.



● Side Panel Clip

The patented tool free installation side panel clip.




● Cooling Fan

Optional 9cm auxiliary cooling fan at rear panel for better system cooling.



● Tool Free Installation and Easy Maintenance

Screw-less front panel, drive bays & I/O slots.



● Folded Edge

For safety installation. No sharp edges, debris.

● Stamped Motherboard Support

No M/B standoffs installation required, for faster M/B installation.

CASE SIZE	Mini Tower Chassis
EXTERNAL DRIVE BAY	5.25" x 2, 3.5" x 2
INTERNAL DRIVE BAY	3.5" x 1, 2.5" x 1
FRONT PORTS	USB2.0 x 2, HD Audio
DIMENSIONS(HxWxD)	363 x 180 x 370mm
w/o Front Panel	14.3" x 7.1" x 14.6"
M/B	Micro-ATX
I/O EXPANSION SLOTS	PCI-E / PCI / AGP Expansion Slot x 4
POWER SUPPLY	ATX 12V Form Factor, PS II
THERMAL SOLUTION	Intel Certified TAC 2.0
COOLING FAN	8 or 9cm Rear Fan
SAFETY	Meets RoHS, CE and FCC Class B Requirements.
SECURITY	Padlock Loop for Padlock / Kensington Slot
OPTIONAL	8 or 9cm Rear Fan / eSATA / Chassis Intrusion Switch USB 3.0 x 2 / 3.5" to 2.5" HDD / SSD Bracket

Specification