

Features

- Stamped Motherboard Support Easy M/B installation - No M/B standoff required.
- Detachable HDD Drive Cage Choose one for standard or two optional cages for better install and service.
- Extra Vent at Rear Panel Optional 9cm or 12cm auxiliary cooling fan can be installed at rear panel for better system cooling.
- Configured up to 9 Drive Bays Expandable to 5.25" x 3, 3.5"x 4 and optional internal 3.5" drive bay x 2.
- Folded Edge
 No sharp edges for safe installation.
- Optional Screwless Side Panels, ODD Bays, FDD Bays and 4 Expansion Slots
 For easy removal and installation.





TAC 2.0 Thermal Solution

CASE SIZE	Mid Tower Chassis
EXTERNAL DRIVE BAY	5.25" x 3, 3.5" x 2
INTERNAL DRIVE BAY	3.5" × 2
FRONT PORTS	USB 2.0 x 2 / Audio
DIMENSIONS (HxWxD)	16.3" x 7.5" x 17.5"
w/o Front Panel	415 x 190 x 445mm
M/B	ATX, Micro ATX
I/O EXPANSION SLOTS	PCI-E / PCI / AGP Slot x 7
POWER SUPPLY	ATX 12V, PSII
THERMAL SOLUTION	Intel Certified TAC 2.0
SAFETY	Meets RoHS, CE and FCC Class B Requirements.
SECURITY	Padlock Loop for Padlock / Kensington Slot
OPTIONAL	Internal HDD Cage for Extra 3.5" Drive Bay x 2
	9 or 12cm Rear Fan / IEEE 1394
	Side Panel Clip / Chassis Intrusion Switch
	Screwless Drive Bays / Screwless I/O Slot
	TOTAL STATE OF THE



EA010

Specification -