



- Stamped Motherboard Support Easy M/B installation - No M/B standoff required.
- Extra Vent at Rear Panel Optional 9cm or 12cm auxiliary cooling fan can be installed at rear panel for better system cooling.
- Configured up to 7 Drive Bays Expandable to 5.25" x 2, 3.5"x 3 and optional internal 3.5" drive bay x 2.
- Folded Edge
 No sharp edges for safe installation.
- Optional Detachable HDD Drive Cage, Screwless Side Panels, ODD Bays and FDD Bays For easy removal and installation.





TAC 2.0 Thermal Solution

EXTERNAL DRIVE BAY	5.25"×2, 3.5"×2
INTERNAL DRIVE BAY	3.5" x I
FRONT PORTS	USB 2.0 x 2 + Audio
DIMENSIONS (HxWxD)	13.8" × 7.5" × 15"
w/o Front Panel	350 x 190 x 380mm
M/B	Micro ATX
O EXPANSION SLOTS	PCI-E/PCI/AGP Slot x 4
POWER SUPPLY	ATX 12V, PSII
THERMAL SOLUTION	Intel Certified TAC2.0
SAFETY	Meets RoHS, CE and FCC Class B Requirements.
SECURITY	Padlock Loop for Padlock / Kensington Slot
OPTIONAL	Internal HDD Cage for Extra 3.5" Drive Bay x 2
	9 or 12cm Rear Fan / IEEE 1394
	Side Panel Clip / Chassis Intrusion Switch
	Screwless Drive Bays

CASE SIZE Mini Tower Chassis

Specification -



EM011